

M45D65B

Power Supply

MEGMEET®
Global Expert In Rectifiers

Mechanics

Mechanics	19-inch width, 5U height
Dimension(mm)	482.0(W)*400.0 (D)*221.7(H)
Weight(Kg)	≤20

Configuration


AC input	3 phase 5 wires 63A/4P
Battery MCB	125A/1P×2
LLVD breakers	16A/1P×1+32A/1P×6+63A/2P×1
BLVD breakers	6A/1P×1+10A/1P×2+16A/1P×2+63A/1P×1

Rectifier module

Module type	MR483000HG2
Specification	Description
AC Input	85Vac ~ 300Vac
Power Factor	0.99
Efficiency	> 96%
DC Output	-42Vdc ~ -58Vdc
Rated voltage	-48Vdc
Nominated voltage	-53.5Vdc

Controller

Controller---MC2600, LCD display, RS485
Alarm: protection, module fault, AC off, SPD fault, Low battery voltage
1000 alarms history
Environment accessing:
Door check, 4 ways temperature, humidity
Control function:
Modules on/off, battery disconnection
Battery management:
Boost/float charge, temperature compensation, battery disconnection, battery self-test, module dormancy



Rectifier module



Controller

MEGMEET®
Globe Expert in Rectifiers

- EV power
- Electric power
- Telecom
- LED screen power

- Medical power
- Industry microwave power
- Solar power
- Flat panel display power

- Air inverter power
- Microwave oven power
- Bathroom power
- Air source heater power

Shenzhen Megmeet Electrical Co.,Ltd

5F, Ziguang Information Harbor, Langshan Road | Shenzhen China 518057
Hotline: 400-666-2163 +86-755-86600500

Megmeet electric company reserves the right to modify the technical parameters and appearance of the products in this catalogue without prior advice to the users.
©2018 Megmeet electrical Ltd. all rights reserved.